


Technical Data

Type	4 Roller
Operation	Cylinder/Key
Pz (mm)	92
Backset (mm)	25, 30, 35, 40, 45
Faceplate (mm)	16 or 24mm U

Material Specification

Lock Case	Steel acc. En 10149/zinc plated
Face Plate	Steel acc. En 10149
Latch Bolt	Zinc diecasting acc. 1743-2/nickel plated En 12540
Deadbolt	Zinc diecasting acc. 1743-2/nickel plated En 12540
Spindle Square	Brass acc. DIN 1709
Handle-Spring Housing	Zinc diecasting acc.. 1743-2/yellow bichromated En 12330
Handle-Spring	Steel acc. DIN 2076-D
Drive Gear	Steel acc. En 10149
Slider	Steel acc. En 10149/zinc plated
Tumbler	Zinc diecasting acc. 1743-2/nickel plated En 12540
Tumbler Spring	Steel acc. DIN 2076-D
Box Quantity	5



AS 8250/9800 4 Roller

Locking system for residential doors where only a basic level of security is required.

The lock is a cylinder/key operated multipoint lock featuring 4 brass roller cams, a reversible latch and an anti-saw deadbolt as standard.

- Key/cylinder operated with day latch facility
- Roller cams compression adjustable +/-1mm
- Suits standard 92mm Pz handles
- Available in a range of backsets and with a 24mm "U-track" faceplate to special order

Part Numbers

Description	Type	Backset (mm)	Rollers	Part No. 24mm U	Part No. 16mm Flat
AS 8250/9800 Multipoint Lock	Standard	25	4	045100*	045322
AS 8250/9800 Multipoint Lock	Standard	30	4	045105*	045324
AS 8250/9800 Multipoint Lock	Standard	35	4	045112	045232
AS 8250/9800 Multipoint Lock	Standard	40	4	045136*	045242*
AS 8250/9800 Multipoint Lock	Standard	45	4	045152*	045252

* Special order only

Guarantees & Accreditations

Mechanical Guarantee	5 years
Labour Guarantee	2 years



to place your order simply call our sales team direct on 01327 312 400